

PRI-ETR-60W

PRI-ETR-100W

PRI-ETR-150W

PRI-ETR-200W

PRI-ETR-300W



Specifications:

Product Code: PRI-ETR-60W
 Frequency: 50/60Hz
 Input Voltage: 170-250VAC
 IP Rating: IP67
 AC Input Inlet: HO3VV-F
 3GO.75mm²
 AC Cable: 1.2m
 Output voltage: 12/24VDC
 Output current: 5A (12V)
 2.5A (24V)
 Max. work Tem. 40°C
 Storage Tem. -25~85°C
 Case Material: Aluminum
 Dimensions: 150X70X50mm
 Certifications: SAA, CE, RoHS
 C-tick

Specifications:

Product Code: PRI-ETR-100W
 Frequency: 50/60Hz
 Input Voltage: 170-250VAC
 IP Rating: IP67
 AC Input Inlet: HO3VV-F
 3GO.75mm²
 AC Cable: 1.2m
 Output voltage: 12/24VDC
 Output current: 8.33A (12V)
 4.16A (24V)
 Max. work Tem. 40°C
 Storage Tem. -25~85°C
 Case Material: Aluminum
 Dimensions: 215X62X50mm
 Certifications: SAA, CE, RoHS
 C-tick

Specifications:

Product Code: PRI-ETR-150W
 Frequency: 50/60Hz
 Input Voltage: 170-250VAC
 IP Rating: IP67
 AC Input Inlet: HO3VV-F
 3GO.75mm²
 AC Cable: 1.2m
 Output voltage: 12/24VDC
 Output current: 12.5A (12V)
 6.25A (24V)
 Max. work Tem. 40°C
 Storage Tem. -25~85°C
 Case Material: Aluminum
 Dimensions: 220X130X63mm
 Certifications: SAA, CE, RoHS
 C-tick

Specifications:

Product Code: PRI-ETR-200W
 Frequency: 50/60Hz
 Input Voltage: 170-250VAC
 IP Rating: IP67
 AC Input Inlet: HO3VV-F
 3GO.75mm²
 AC Cable: 1.2m
 Output voltage: 12/24VDC
 Output current: 16.6A (12V)
 8.33A (24V)
 Max. work Tem. 40°C
 Storage Tem. -25~85°C
 Case Material: Aluminum
 Dimensions: 220X130X63mm
 Certifications: SAA, CE, RoHS
 C-tick

Specifications

Product Code: PRI-ETR-300W
 Frequency: 50/60Hz
 Input Voltage: 180-250VAC
 IP Rating: IP67
 AC Input Inlet: HO3VV-F
 3GO.75mm²
 AC Cable: 1.2m
 Output voltage: 12/24VDC
 Output current: 12.5A (24V)
 Max. work Tem. 40°C
 Storage Tem. -25~85°C
 Case Material: Aluminum
 Dimensions: 280X87X33mm
 Certifications: SAA, CE, RoHS
 C-tick

