

PRI-700-8.4W

PRI-JA-10W

PRI-TR-12W

PRI-ETR-20W

PRI-ETR-36W



Specifications:

Product Code: PRI-700-8.4
 Frequency: 50/60Hz
 Input Voltage: 100-240VAC
 Output voltage: 12VDC
 Output current: 700mA
 DC Cord: 2468#20AWG
 DC Plug: OD: 5.5mm
 ID: 2.5mm
 DC Cable: 1.2m
 Max. work Tem. 40°C
 Storage Tem. -25~85°C
 Case Material: 94V-0 ABS+PC
 PCB Material: 94V-0
 Dimensions: 72X40X50mm
 Certifications: SAA, C-tick

Specifications:

Product Code: PRI-JA-10W
 Frequency: 50/60Hz
 Input Voltage: 100-240VAC
 Output voltage: 12/24VDC
 Output current: 0.83A (12V)
 0.42A (24V)
 DC Cord: 2468#20AWG
 DC Plug: OD: 5.5mm
 ID: 2.5mm
 DC Cable: 1.2m
 Max. work Tem. 40°C
 Storage Tem. -25~85°C
 Case Material: 94V-0 ABS+PC
 PCB Material: 94V-0
 Dimensions: 80X45X50mm
 Certifications: SAA, C-tick

Specifications:

Product Code: PRI-TR-12W
 Frequency: 50/60Hz
 Input Voltage: 100-240VAC
 AC Input Inlet: IEC320-C8
 AC Cable: 1.2m
 Output voltage: 12V
 Output current: 1A (12V)
 DC Cord: 2468#20AWG
 + MR16 Base
 DC Cable: 1.2m
 Max. work Tem. 40°C
 Storage Tem. -25~85°C
 Case Material: 94V-0 ABS+PC
 PCB Material: 94V-0
 Dimensions: 83X40X30mm
 Certifications: SAA, CE, RoHS
 GS, TÜV

Specifications:

Product Code: PRI-ETR-20W
 Frequency: 50/60Hz
 Input Voltage: 170-250VAC
 IP Rating: IP67
 AC Input Inlet: HO3VV-F
 3GO.75mm²
 AC Cable: 1.2m
 Output voltage: 24VDC
 Output current: 0.83A (24V)
 Max. work Tem. 40°C
 Storage Tem. -25~85°C
 Case Material: Aluminum
 Dimensions: 162X31X20mm
 Certifications: SAA, CE, RoHS
 C-tick

Specifications:

Product Code: PRI-ETR-36W
 Frequency: 50/60Hz
 Input Voltage: 170-250VAC
 IP Rating: IP67
 AC Input Inlet: HO3VV-F
 3GO.75mm²
 AC Cable: 1.2m
 Output voltage: 12VDC
 Output current: 3A (12V)
 Max. work Tem. 40°C
 Storage Tem. -25~85°C
 Case Material: Aluminum
 Dimensions: 189X31X20mm
 Certifications: SAA, CE, RoHS
 C-tick

