



## Specifications

Power:	2.9W per meter
Voltage:	12/24VDC, 240VAC
Colour:	Cool white, Warm White Blue, Green, Pink, Red, RGB
Cover:	PVC
LED QTY:	36pcs per meter
Waterproof:	IP65
Lifetime:	50,000 hours
Diameter:	13mm

## Assembly Cutting & Connecting



Identify the embossed cutting Mark. Cut through mark area.



Use silicon in the END CAP to seal from moisture.



Push connector firmly and deeply into copper wires with pins.



Screw together after connector pins are in place.



Accessories  
Power connector, End Cap, Clips

**All installation must be done by a qualified and licensed Electrician.**

**PRI-ROPE is available in Varieties of Colours.**

## Wiring Instruction

- 1 Do not turn the light on before finishing the process of installation
- 2 Do not turn the light on when light on the reel, stacked into agglomerate or been covered.
- 3 Please cut the light at cutting marks which are marked on surface of the rope, otherwise, it will be at least one unit not working; also the cutting point must be neat, in case of short circuiting.
- 4 Do not hit the rope light body with hammer or other solids.
- 5 Please install the rope light with the matched fittings, such as plastic mounting clips (PRI-CLIP-R or PRI-CLIP-RR), and do not twist the light body.
6. Please use the cap cover at the end of the light and apply sealant, in order to prevent water penetration.
7. It can be connected between each light body only if they are the same specification and voltage, but the whole length does not go beyond the limited connecting length.
8. Please use according to the right picture when you bend the light body in installation.

