

**PRI-TR-24W**

**PRI-TR-36W**

**PRI-TR-60W**

**PRI-TR-84W**

**PRI-TR-116W**



**Specifications:**

Product Code: PRI-TR-24  
 Frequency: 50/60Hz  
 Input Voltage: 100-240VAC  
 AC Input Inlet: IEC320-C8  
 AC Cable: 1.2m  
 Output voltage: 12VDC  
 Output current: 2A (12V)  
 DC Cord: 2468#20AWG  
 DC Plug: OD: 5.5mm  
 ID: 2.5mm  
 DC Cable: 1.2m  
 Max. work Tem. 40°C  
 Storage Tem. -25~85°C  
 Case Material: 94V-0 ABS+PC  
 PCB Material: 94V-0  
 Dimension: 95X42X28mm  
 Certifications: SAA, CE, RoHS  
 GS, TÜV

**Specifications:**

Product Code: PRI-TR-36  
 Frequency: 50/60Hz  
 Input Voltage: 100-240VAC  
 AC Input Inlet: IEC320-C8  
 AC Cable: 1.2m  
 Output voltage: 12/24VDC  
 Output current: 3A (12V)  
 1.5A (24V)  
 DC Cord: 2468#20AWG  
 DC Plug: OD: 5.5mm  
 ID: 2.5mm  
 DC Cable: 1.2m  
 Max. work Tem. 40°C  
 Storage Tem. -25~85°C  
 Case Material: 94V-0 ABS+PC  
 PCB Material: 94V-0  
 Dimension: 115X48X30mm  
 Certifications: SAA, CE, RoHS  
 GS, TÜV

**Specifications:**

Product Code: PRI-TR-60  
 Frequency: 50/60Hz  
 Input Voltage: 100-240VAC  
 AC Input Inlet: IEC320-C8  
 AC Cable: 1.2m  
 Output voltage: 12/24VDC  
 Output current: 5A (12V)  
 2.5A (24V)  
 DC Cord: 2468#20AWG  
 DC Plug: OD: 5.5mm  
 ID: 2.5mm  
 DC Cable: 1.2m  
 Max. work Tem. 40°C  
 Storage Tem. -25~85°C  
 Case Material: 94V-0 ABS+PC  
 PCB Material: 94V-0  
 Dimension: 115X48X30mm  
 Certifications: SAA, CE, RoHS  
 GS, TÜV

**Specifications:**

Product Code: PRI-TR-84  
 Frequency: 50/60Hz  
 Input Voltage: 100-240VAC  
 AC Input Inlet: IEC320-C8  
 AC Cable: 1.2m  
 Output voltage: 12/24VDC  
 Output current: 7A (12V)  
 3.5A (24V)  
 DC Cord: 2468#20AWG  
 DC Plug: OD: 5.5mm  
 ID: 2.5mm  
 DC Cable: 1.2m  
 Max. work Tem. 40°C  
 Storage Tem. -25~85°C  
 Case Material: 94V-0 ABS+PC  
 PCB Material: 94V-0  
 Dimension: 140X48X32mm  
 Certifications: SAA, CE, RoHS  
 GS, TÜV

**Specifications:**

Product Code: PRI-TR-116  
 Frequency: 50/60Hz  
 Input Voltage: 100-240VAC  
 AC Input Inlet: IEC320-C8  
 AC Cable: 1.2m  
 Output voltage: 12/24VDC  
 Output current: 9.66A (12V)  
 4.33A (24V)  
 DC Cord: 2468#20AWG  
 DC Plug: OD: 5.5mm  
 ID: 2.5mm  
 DC Cable: 1.2m  
 Max. work Tem. 40°C  
 Storage Tem. -25~85°C  
 Case Material: 94V-0 ABS+PC  
 PCB Material: 94V-0  
 Dimension: 168X73X42mm  
 Certifications: SAA, CE, RoHS  
 GS, TÜV

